## COMPO-CARE

## **COMPOSITE WOOD REVIVER**

Product description	COMPO-CARE is a water-based reviver for all composite woods. Protecting, enhancing and reviving the colour of composite wood, COMPO-CARE is easy to apply and quick drying.
Properties	<ul> <li>Transparent tinted coating.</li> <li>Enhances the colour of composite wood.</li> <li>Protects against staining (oil, grease).</li> <li>Waterproofs the surface.</li> <li>Easy to apply.</li> <li>Quick drying.</li> <li>Low odour.</li> </ul>
Basic uses	<ul> <li>Exterior.</li> <li>All composite woods.</li> <li>Vertical and horizontal surfaces: decks, cladding, garden furniture.</li> <li>Ideal for grooved decking.</li> </ul>
Technical data	Finish: Matt/Matt Sheen. Vehicle Type: Acrylic. Solvent Type: Water. Specific Gravity (at 20°C): 1.080 $\pm$ 0.05. Physical State: Liquid. Solid Content: 6% w/w. Flash point: Not classed as flammable. Shelf Life: 1 year minimum in original unopened packaging. Container Size: 1L, 2.5L. Colour(s): $\int_{Brown}$ $\int_{Grey}$ Drying time(s): • Touch dry - 1 hour. • Fully dry - 12 -24 hours depending on temperature and humidity. • Decks subject to heavy traffic should be left 24 hours before being put back in to full service. VOC: 3% $\pm$ 0.5.
Application tools	Brush: High quality synthetic brush. Roller: Synthetic woven cover.
Good application practice	Do not apply in direct sunlight or to hot surfaces. Do not apply if cold and/or wet weather is expected within 24 hours. Apply between 10°C and 30°C. Cover and protect everything you do not wish to coat. For colour uniformity, mix all product together that is to be applied to any one area or section. Always work the entire length of a deckboard or cladding board to a logical break. Vertical cladding should be coated from top to bottom. Never stop application in the middle of the board.
Surface preparation	Surfaces must be clean, dry and free of dirt, grease, oil, mildew and stains. Treat mildew with a 50/50 bleach/water solution. Scrub solution on to surface and allow to stand for 10-15 minutes rinse thoroughly. After cleaning allow wood to thoroughly dry or until it has reached a moisture content of 18% or less before applying the finish. Clean surface with COMPO-CLEAN*.

Application	Do not dilute. Stir product thoroughly before and periodically during application. Apply a single, even coat of COMPO-CARE to the entire length or piece of wood, stopping at any natural breaks to avoid lapping.
Coverage	15 m <sup>2</sup> per litre. Actual coverage will vary depending on application method, type, texture, age and porosity of the wood.
Maintenance	This will depend on exposure to the sun, weather and foot traffic. Maintenance is due when treated areas turn clear. COMPO-CARE requires no sanding or stripping prior to the application of a maintenance coat. Clean surface with COMPO-CLEAN*. Apply a single application of COMPO-CARE to the entire surface according to the "Application" instructions above.
Clean-up	Soap and water.
Storage	Keep from freezing and high temperatures.
General information	Every care is taken to ensure that the information provided in this technical data sheet is accurate. OWATROL INTERNATIONAL is unable to guarantee results as we have no control over the conditions under which our products are applied. For further advice and information please contact our technical department by email at info@owatrol.com or the local OWATROL Agent for your country. The information above is correct at the date of issue. All other OWATROL products named in this document should be used as per label instructions and the technical data sheet.
Safety	Refer to the safety data sheet (MSDS) available at <b>www.owatrol.com</b> and text on the packaging. Keep out of the reach of children.
Issue date	June 2013.

\* Same manufacturer

The information set out cons are purely illustrative and are not the responsibility of the manufacturer, the application of products not made under his supervision.



OWATROL INTERNATIONAL SLU Barcelona - Spain Tel. +34 93 125 88 68 Fax +34 93 106 02 13



Find all our solutions: www.owatrol.com