

OWATROL®

DEKS OLJE D2®

EXOTIC WOOD FINISH

USAGE

- For use on woods pre-treated with DEKS OLJE D1® (or OWATROL OIL® or XYLKOTE interior oil).
- Exterior: garden furniture, fences, stairs, boats etc.
- Interior: doors, windows, stairs, bathrooms, frames etc.
- Horizontal and vertical surfaces.
- Hardwoods and exotic tropical woods such as teak, ipé, bovinga, bolondo and iroco.
- On boats, DEKS OLJE D2® can be used for all applications above the water line.

HIGH GLOSS FINISH FOR INTERIOR AND EXTERIOR

- Light and resistant film that avoids peeling, scaling, cracking or blistering.
- High gloss, very durable finish.
- Flexible finish (like varnish) which does not hide the wood grain.
- Easy maintenance, simply wash regularly with water.
- Fast refurbishing, no sanding between coats.



RECOMMENDATIONS PRIOR TO APPLICATION

- Wood should be treated with DEKS OLJE D1® prior to DEKS OLJE D2®. In some cases OWATROL OIL® or XYLKOTE interior oil may be used.
- The wood surface should be clean and dry.
- Do not dilute.



APPLICATION

- Apply 3 to 6 coats of DEKS OLJE D2® depending on exposure of surface.
- Allow at least 12 hours drying between coats.
- There is no need for sanding between coats.
- Allow 3 to 4 days drying before putting surface in use.

Note: Clean any dripping or drops of DEKS OLJE D2® from surface before the product dries. Once dry, spots will form and they will be very hard to eliminate.

COVERAGE	APPLICATION TOOLS	TEMPERATURE FOR APPLICATION	DRYING TIME	CLEAN UP
15 m ² /l		+35°C +5°C	24 hours SETTING UP TIME BEFORE USE 3 days	WHITE-SPIRIT INTERIOR EXTERIOR

**Owatrol International SL**C/Aragón 179, 5º - 08011 Barcelona - Spain
Tel: +34 934 51 66 04 - Fax: +34 934 52 14 54
info@owatrol.com - www.owatrol.com